

Tank Gauging System with Two or Four Analog 4-20 mA Level Transducer Inputs and Secondary Containment Leak Detection



Product Description

The TMS2000A1 utilizes much of the functionality and all of the proven reliability of the TMS2000 magnetostrictive Tank Management System in a console designed to accept level data in 4-20 mA format from a broad range of level sensor technologies, including ultrasonic, microwave and hydrostatic pressure, well-suited for non-contact or sticky liquids, grease, powder or granular dry goods. The TMS2000A1 is available in either 2 Transducer/2 Leak Sensor or 4 Transducer/4 Leak Sensor configurations, with all of the I/O, communications and enclosure options of the TMS2000 series.

Console

- Dimensions (W x H x D): 11.8" x 11.5" x 4.75" (300 mm x 292 mm x 121 mm)
- Weight: 14 lb (6.4 kg) (w/ Printer)
- Operating Temperature: -40 °F to 160 °F (-40 °C to 70 °C) w/o Printer
-5 °F to 140 °F (-20 °C to 60 °C) w/ Printer
- Humidity: 95% Non-condensing
- Enclosure Rating: Locking NEMA 12 (IP52), NEMA 4 (IP56) or NEMA 4X (IP66) (304 SS)
- Power Requirements: 115/230 VAC $\pm$ 15% (w/o Printer) Switchable, 50-60 Hz, 20 W Max.
8-16 VDC or 16-60 VDC Optional
- Memory: Configuration / Setup Data – EEPROM, 50 year data retention, no batteries
Log Reports and Real-Time Clock – Lithium Battery-Backed RAM, 5-10 year data retention
- Audible Alarm: 85 db
- Display: 9-Character, Super Bright LED Data Display, Readable from 25' (7.6 m)
Ultra-High Intensity Alarm LEDS, Visible from 75' (22.9 m)
Display data includes Product Level, Gross Volume, % Volume, and Ullage
- Communications: RS-232 Included Standard, RJ-13 Jack
RS-485 Included Standard, RJ-13 Jack (For Pneumercator Peripherals)
Internal, Secured Modem, Fax / Modem, Network Interface, or ModBus Optional
- Probe / Sensor Capacities: 2 or 4 Two-Wire, 4-20 mA Input Level Sensors (Ultrasonic, Microwave, Pressure, Etc.)
2 or 4 Dry Contact Leak/Point Level Sensor Inputs
- I/O, Non-Haz.: Standard: 2 Relays, 1 Form C, Rated 10 A@120 VAC, 6 A@240 VAC, w/ 2 Opto-Isolated Inputs
Expansion Options: (1 slot available)
4 Relays, 1 Form C, Rated 10 A@120 VAC, 6 A@240 VAC, w/ 4 Opto-Isolated Inputs
8 Relays, 1 Form A, Rated 5 A@120 VAC, 5 A@240 VAC w/ 8 Opto-Isolated Inputs
16 Relays, 1 Form A, Rated 5 A@120 VAC, 5 A@240 VAC
6 or 12-Ch. Programmable Analog Outputs:
0-1 mA, 0-20 mA, 0-24 mA, 4-20 mA, 0-5 VDC, 1-5 VDC



Pneumercator Company, Inc.
1785 Expressway Drive North
Hauppauge, New York 11788

Tel: (631) 293-8450
Fax: (631) 293-8533
<http://www.pneumercator.com>

Transducers (See individual transducer specification sheets for detailed information)

- Technologies: Air Ultrasonic, Microwave, Hydrostatic Pressure, Two-Wire 4-20 mA Current Loop
- Field Wiring: 22AWG, 2-Conductor twisted pair w/ shield
Belden 8441, Belden 8761, Alpha 1736C or equiv., maximum length 1000' (305 m)
- Models: Ultrasonic, UT420-360 max. tank height 30' (9.1 m)
Microwave, MT420-960 max. tank height 80' (24.4 m)
Pressure, PT420-xxx max. tank height 100' (30.5 m)

Sensors

- LS600LD Float, Containment, Manway and Piping Sumps, Dispenser Pan
- LS600xx Multi-Float, High / Low Level and Pump Control
- RSU800 Float, Wet Annular / Reservoir
- LS610 Float, Dry Annular

Remote Displays/Annunciators

- ETD1000T Addressable (up to 16), Multi-Drop, Touchscreen-Based, Remote Electronic Tank Display Panel
 - ETD1000 Addressable (up to 16), Multi-Drop, Remote Electronic Tank Display Panel
 - RA400 Addressable (up to 16), Multi-Drop, Programmable Remote Audible/Visual Alarm Panel
 - ETD1000W Wireless Remote Electronic Tank Display Panel*
 - RA400W Wireless Programmable Remote Audible/Visual Alarm Panel*
- *Note: MPX200 Master Peripheral Expansion Module required.

Certifications / Approvals

- UL/cUL – System designed in accordance with UL/cUL, but not presently listed.
- FCC Part 15B, Part 68

Model Numbers

- TMS2000A11 – Two 4-20 mA Inputs / Two Sensor Inputs
- TMS2000A12 – Four 4-20 mA Inputs / Four Sensor Inputs