Rigid Magnetostrictive Probe, EPA Compliant*



Product Description

The MP450S Level Gauging Probe utilizes proven Magnetostrictive technology for accuracy and reliability. When used in conjunction with the TMS2000/3000/4000, it provides the ability to perform EPA compliant in-tank leak tests in underground storage tanks. The probe is available in lengths up to eighteen feet.

Applications

- Above and Below Ground Storage Tanks
- Bulk Storage Tanks
- Generator Sub Base Tanks

Specifications

Technology: Magnetostrictive, Dual Float, w/ reflection resolution doubling Accuracy (Minimum): Product Level: 0.0005" (0.013 mm) 0.001" (0.025 mm) Water Level: Temperature: 0.001 °F (0.0006 °C) Materials: Shaft: 316 SS Floats: Buna-N (Optional 316 SS or Urethane) Minimum 2" (51 mm) dia. riser, 4" (102 mm) dia. riser required for in-tank leak Riser Mount: Direct Mount: Minimum 2" (51 mm) opening with bushing or flange mount Probe Lengths: 1'-18' (305 mm - 5486 mm) 6 Thermistors; 5 in shaft, 1 in probe head Temperature Sensing: Location Approval: UL Class I, Div 1, Groups C and D; cUL Class I, Zone 0, Group IIB **Operating Temperature:** -40 °F to 175 °F (-40 °C to 80 °C) **Operating Pressure:** 150 PSIG (1034 kPa) Field Wiring: 22AWG, 2-Conductor twisted pair w/ shield Belden 8441, 8761, Alpha 1736C or equiv., maximum length 3000' to 4600' (914 m to 1402 m) Compatible With: TMS2000, TMS3000, TMS4000 Installation

Probes 15' (4.6 m) or less in length can be installed into a vertical riser pipe with the probe foot contacting the tank bottom, or direct-mounted at the tank top via a ³/₄" NPT compression fitting kit. Probes greater than 15' (4.6 m) must be direct-mounted.

Certifications/Approvals

- UL/cUL Approved*, File #E139464
- Third-Party Approved, EPA-Compliant for In-Tank Leak Testing:*
- * When used in conjunction with the TMS2000/3000/4000 series controllers

Note: Specifications subject to change without notice. 10-07-2022



Pneumercator Company, Inc. 1785 Expressway Drive North Hauppauge, New York 11788

Tel: 631-293-8450 Fax: 631-293-8533 www.pneumercator.com

• Oil / Water Separators (See MP452S Series spec)

- All Petroleum Products
- Most Chemical Solvents