


Solid-State, Electro-Optic Secondary Containment Leak Sensor for Chemical Applications with Fault Detection

Chemical Resistant



Outline Specifications



Product Description

The Model ES825-300CFL is a solid-state, electronic leak sensor utilizing electro-optic technology to detect the presence of liquids in secondary containment applications. The “C” version includes all of the features of the standard ES825-300FL, with the addition of a chemical-resistant sensor body and cable resistant to most acids, alkalines and solvents. The sensor contains no moving parts, is unaffected by vapors, and due to its compact size is ideal for interstitial spaces. The ES825-300CFL is functionally identical to the ES825-100CF with the exception that it is specified for connection to both the WiDAM Wireless Data Acquisition Module for TMS wireless applications and the TMS1000 Series. As with the –100CF, the ES825-300CFL supports Pneumercator’s FAULT-DETECT supervised wiring technology, which automatically detects sensor or field wiring faults.

Applications

- Dry Annular Space in Double-Wall Tanks
- Containment, Manway and Piping Sumps

Specifications

- Technology: Electro-optic, no moving parts
- Wetted Materials: PFA Teflon, FEP Teflon, Epoxy, and Polypropylene
- Operating Temperature: -40 °F to 175 °F (-40 °C to 80 °C)
- Cable: 22AWG, 3-Conductor, FEP Teflon Jacket, 20’ Length
- Pass-thru NPT/BSPT Opening Size: Minimum 3/4”
- Location Approval*: UL Class I, Div 1, Groups C and D; cUL Class I, Zone 0, Group IIB
- Compatible with: TMS1000, TMS2000W/WiDAM, TMS4000W/WiDAM

Installation

Sensor may be suspended by its cable, placed on the containment or sump floor, or thru-wall mounted via a 1/4” FNPT opening. For dry annular applications, sensor may be pulled through using fish tape attached to sensor pull ring, or pushed through with a section of 1/2” ENT (not included) attached to the back end of the sensor.

Certifications/Approvals

- UL/cUL Approved*, File #E139464
- Third-Party EPA Listed*

* When used in conjunction with the TMS2000W/TMS4000W series WiDAM Wireless Data Acquisition Module

Note: Specifications subject to change without notice. 10-07-2022



Pneumercator Company, Inc.
1785 Expressway Drive North
Hauppauge, New York 11788

Tel: 631-293-8450
Fax: 631-293-8533
<http://www.pneumercator.com>