

Remote Audible / Visual Alarm Annunciator In NEMA 4X (IP56) Enclosure



RA200



RA200PM



RS2

Product Description

The RA200 series Remote Annunciator is used in applications where it is desired to have access to audible and optional visual alarms from an on-sight location remote to the TMS tank management console. The RA200 replicates critical alarm warnings, and is typically used in applications where both operational personnel in the active service area and supervisory personnel in a remote office require immediate warning of critical alarms, or where critical alarm warnings are required at both on-sight indoor and outdoor locations. The optional RS2 can be used to test the annunciator as well as reset the audible alarm from a remote location.

Specifications

- Dimensions (W x H x D): 5.13" x 5.13" x 4.75" (130 mm x 130 mm x 120 mm) (RA200)
3.54" x 4.53" x 2.17" (90 mm x 115 mm x 55 mm) (RA200PM)
2.55" x 4.53" x 2.62" (65 mm x 115 mm x 67 mm) (RS2)
- Weight: 1.15 lb (0.5 kg) (RA200)
1.05 lb (0.5 kg) (RA200PM)
0.4 lb (0.2 kg) (RS2)
- Operating Temperature: -31 °F to 150 °F (-35 °C to 66 °C)
- Humidity: 100%, Non-condensing
- Enclosure Rating: NEMA 4X (IP56)
- Power Requirements: 115/230 VAC Switchable, 50-60 Hz, 8 W Max.
- Audible Alarm: 110 dba at 3 feet (1 m)
- Visual Alarm: 15 candela (Amber)

Model Numbers

- RA200K RA200 with RA200PM
- RA200KR RA200 with RA200PM and RS2